

MicroAir Specifications

Ultra Low Air Pressure Regulators and Controllers

On Line Controls, Inc.
www.onlinecontrols.com

Series	Model	Range/Max Output	Power Inputs	Control Inputs	Functionality	Options	Case Dimensions H x W x D								
MicroAir I	MAI	0-2 in wc/ 5 SCFH 0-3 in wc/ 6 SCFH 0-5 in wc/ 11 SCFH 0-10 in wc/20 SCFH 0-15 in wc/ 25 SCFH 0-30 in wc/40 SCFH 0-2 psi/55 SCFH 0-3 psi/ 70 SCFH 0-5 psi/90 SCFH	110/220 VAC 50/60 Hz Selectable 3 conductor grounded IDC power cord (supplied)	N/A	30 turn manual	N/A	12" x 10" x 6"								
Dual MicroAir I	DMAI						16" x 10" x 6"								
MultiAir 3-channel MicroAir I	MU3MAI						23" x 12" x 6"								
MicroAir II	MAII						Additional ranges quoted upon request MAX 5 psi (in wc = inch of water column; SCFH= Standard Cubic Feet per hour)	3 Internal screw terminals Up / Down /Gnd Up/Down Inputs Open: Inactive Close to Gnd: Active	*Up/Down Manual control push buttons *Motorized Up/Down remote control ready for solid state or mechanical relays	*Additional (LED) Digital pressure readout *1-6 VDC pressure output *4-20 ma pressure output *Remote Control Unit	12" x 10" x 6"				
Dual MicroAir II	DMAII										16" x 10" x 6"				
MultiAir 3-channel MicroAir II	MU3MAII										23" x 12" x 6"				
MicroAir IV	MAIV										Additional ranges quoted upon request MAX 5 psi (in wc = inch of water column; SCFH= Standard Cubic Feet per hour)	2 Internal screw terminals +/- +Input Analog Control 0 to 10 VDC Dual State Control Close to - or 0 to +1 VDC: High Open or +4 to +24 VDC: Low	*10 turn manual control potentiometer * Hi speed motorized Up/Down remote control ready for 0-10 VDC signal * Hi speed motorized dual pressure remote switching	*Additional (LED) Digital pressure readout *1-6 VDC pressure output *4-20 ma pressure output *NEW option Contact closure (Up/down inputs)	12" x 10" x 6"
Dual MicroAir IV	DMAIV														16" x 12" x 6"
MultiAir 3-channel MicroAir IV	MU3MAIV														22" x 13" x 6"
MultiAir 4-channel MicroAir IV	MU4MAIV														28" x 10" x 6"

- All units include 4 1/2" Magnehelic meter pressure readout.
- All units accept 1/4 male NPT fitting for input and output of air
- MicroAir units (single channel) require 45 psi +/- 10% @ 2.5 SCFM
- Leftside in/ Rightside out (keep clear)
- Dual and MultiAir units require 55 psi +/- 10% @ 2.5 SCFM/ per channel

Mounting

- Vertical mounting is essential
- Four 5/16" diameter holes will accommodate both 1/4" and 5/16" mounting bolts.



On Line Controls, Inc.
9A Kane Industrial Dr.
Hudson, MA 01749-2905

Tel: 978-562-5353
Fax: 978-562-8986
olc@onlinecontrols.com